POWER PRODUCTS UGANDA LIMITED

PRODUCT SPECIFICATIONS



Rubaga Kabusu

Plot 103 Rubaga Kabusu Kampala - Masaka Road

Telephone Number(s)

+256 414 341174 | +256 392 176430 +256 758 383266 | +256 758 383340

Emails

sales@powerproductsugandaltd.com info@powerproductsugandaltd.com

KM170F

DESCRIPTION

The drive gear design is incorporated into the engine which will greatly reduce vibration and noise. The precision machined and precisely timed injection pump and the direct-injection design leads to lower fuel consumption and reduced tailpipe emissions.



The high efficiency muffler system greatly lowers exhaust noise. The design or the cylinder block, engine cover, and valve train all combine to reduce engine noise levels.

SPECIFICATION	
Type / Category	Engines & Motors
Engine Type	Single-cylinder, vertical, air-cooled, 4-stroke, direct injection
Bore × Stroke	70 × 55 mm
Displacement	0.211 L
Compression ratio	20:1
Rated power/ Rated speed	2.5 kW/3000 r/min, 2.8 kW/3600 r/min
Lowest rotation speed at zero load	1300 r/min
Lubricating system	Pressure splashed
Starting Method	Recoil starter/Electric starter
Fuel Tank Capacity (L)	2.5 L
Lube oil type	CD grade or SAE 10W-30, 15W-40
Lube Oil Capacity (L)	0.75 L
Weight (kg)	27

Rubaga Kabusu

Plot 103 Rubaga Kabusu Kampala - Masaka Road

Telephone Number(s)

+256 414 341174 | +256 392 176430 +256 758 383266 | +256 758 383340

Emails

sales@powerproductsugandaltd.com info@powerproductsugandaltd.com