

POWER PRODUCTS UGANDA LIMITED

PRODUCT SPECIFICATIONS



HONDA GX160TI

Rubaga Kabusu

Plot 103 Rubaga Kabusu
Kampala - Masaka Road

Telephone Number(s)

+256 414 341174 | +256 392 176430
+256 758 383266 | +256 758 383340

Emails

sales@powerproductsugandaltd.com
info@powerproductsugandaltd.com

DESCRIPTION

The GX160TI engine is suitable for a wide range of heavy duty applications such as in construction equipment, tillers, generators, welders, pumps and other industrial applications. Engine features: OHV design enhances combustion efficiency. High power-to-displacement ratio. Easy starting with an automatic decompression system and an easy-to-grip soft recoil starter handle. High quality materials and purpose-built components which ensure reliable, long-term use. Meets world's most stringent environmental legislation. Low fuel and oil consumption. Reduced vibration and noise levels.



SPECIFICATION

Type / Category	Engines & Motors
Engine Type	Air cooled 4-stroke OHV petrol engine, horizontal shaft, cast iron sleeve
Bore x Stroke	68x45 mm
Displacement	163cm ³
Compression ratio	9.0:1
Rated power/ Rated speed	3.6kw(4.8HP)/3000rpm
Starting Method	Recoil starter
Fuel Tank Capacity (L)	3.1ltrs
Fuel Consumption	1.4l/hr-3600rpm
Lube Oil Capacity (L)	0.6ltr
Weight (kg)	17.1

Rubaga Kabusu

Plot 103 Rubaga Kabusu
Kampala - Masaka Road

Telephone Number(s)

+256 414 341174 | +256 392 176430
+256 758 383266 | +256 758 383340

Emails

sales@powerproductsugandaltd.com
info@powerproductsugandaltd.com