

POWER PRODUCTS UGANDA LIMITED

PRODUCT SPECIFICATIONS



CORGHI TYRE CHANGERS

Rubaga Kabusu

Plot 103 Rubaga Kabusu
Kampala - Masaka Road

Telephone Number(s)

+256 414 341174 | +256 392 176430
+256 758 383266 | +256 758 383340

Emails

sales@powerproductsugandaltd.com
info@powerproductsugandaltd.com

PROLINE 322

DESCRIPTION

- Air operating tilting of column
- Mechanical balancing of tool-holder shaft
- Simultaneously tool alignment with clamping by simply pressing a button
- Double acting bead breaker cylinder



SPECIFICATION

Type / Category	Tyre Changers
Weight	255 kg
Bead-breaker opening	400 mm
Inside clamping capacity	12000 N
Inside clamping capacity	12" ÷ 24"
Max. wheel diameter	1140 mm (44.5")
Max. wheel width	350 mm (14")
Motor Power	0.75 kW
Noise level when running	< 70 dB (A)
Outside clamping capacity	10" ÷ 22"
Power Supply	230 V - 1 Ph - 50 Hz
Chuck rotation speed	6 r.p.m.
Max. chuck rotation torque	1100 Nm
Working pressure	8 ÷ 10 bar

Rubaga Kabusu

Plot 103 Rubaga Kabusu
Kampala - Masaka Road

Telephone Number(s)

+256 414 341174 | +256 392 176430
+256 758 383266 | +256 758 383340

Emails

sales@powerproductsugandald.com
info@powerproductsugandald.com