

POWER PRODUCTS UGANDA LIMITED

PRODUCT SPECIFICATIONS



SPERONI WATER PUMP

Rubaga Kabusu

Plot 103 Rubaga Kabusu
Kampala - Masaka Road

Telephone Number(s)

+256 414 341174 | +256 392 176430
+256 758 383266 | +256 758 383340

Emails

sales@powerproductsugandaltd.com
info@powerproductsugandaltd.com



DESCRIPTION

Multistage submersible pump for 6 inch wells suitable for civil and industrial purposes, food, irrigation plants, in fire installations and for a clean water supply.

SPECIFICATION

Type / Category	Shallow Well Pumps
Pump Type	Multistage Submersible Pump
Operating condition	<ul style="list-style-type: none"> - Liquid temperature up to 35°C (for home use according to EN 60335-2-41) Temperature max. liquid: 35°C (for other uses) - Submersion depth 20 mt - Sand content 40 g/m³ - Start/hour 45 max
Electric Motor	<ul style="list-style-type: none"> - Single-phase 230V-50Hz - Two-Pole induction motor (n = 2850 min⁻¹) - Built-in overload motor protector with automatic reset
Pump Materials	<ul style="list-style-type: none"> - Insulation Class F - Protection IP 68 - Minimum Efficiency Index (BEP) MEI ≥ 0,4
Pump Materials	<ul style="list-style-type: none"> - External pump body: Stainless Steel AISI 304 - Suction strainer: Stainless Steel AISI 304 - Impeller and diffusors: Noryl - Bearing brackets: Cast Iron - Shaft: Stainless Steel AISI 304 - Motor housing: Stainless Steel AISI 304 - Mechanical seal with oil chamber: Silicon/Silicon/NBR

Rubaga Kabusu

Plot 103 Rubaga Kabusu
Kampala - Masaka Road

Telephone Number(s)

+256 414 341174 | +256 392 176430
+256 758 383266 | +256 758 383340

Emails

sales@powerproductsugandaltd.com
info@powerproductsugandaltd.com